

## 6011 Tetrakem FS Ceiling Plus

<b>Product</b>	Flat waterborne acrylate dispersion paint with IMO fire classification. Extremely good opacity.
<b>Suitability</b>	As a primer and topcoat for ceilings with fire classification and as a primer on indoor wall surfaces. Suitable for use on concrete, plaster and filler surfaces, along with different kinds of wood, chip, plywood and mineral boards, plasterboards, fibreglass wallpapers for painting as well as previously painted ceilings and indoor walls.
<b>Certificate</b>	Certificate NO VTT-C-11764-15-16
<b>Properties</b>	<p>Properties of 6011 Tetrakem FS Ceiling Plus paint:</p> <ul style="list-style-type: none"> <li>• IMO (MED Marine Equipment Directive)</li> <li>• Extremely good opacity, one application is usually sufficient</li> <li>• Solvent-free paint</li> <li>• Does not yellow with age</li> <li>• Suitable on ceiling and wall surfaces</li> <li>• AP base can be tinted</li> <li>• Manufactured in Finland</li> </ul>



### Technical data

<b>Dry matter content</b>	App. 58 %
<b>Density</b>	1.40 g/ml
<b>Gloss group</b>	RT6, flat
<b>MT group</b>	2012 MT211, 311 and 2001 MT 30
<b>Wear resistance</b>	Fair, withstands over 2,000 scrubblings. SFS3455.
<b>Tinting</b>	Using common indoor paint colour charts. The AP base paint can be tinted in light shades.
<b>Storage</b>	36 months in the original package, store in a dry and cool place, with temperatures of +5 to +25 °C.
<b>Coverage</b>	<p>Previously painted surfaces 8–12 m<sup>2</sup>/l</p> <p>Wood and building board surfaces 6–10 m<sup>2</sup>/l</p> <p>Concrete, plaster and filler surfaces 5–7 m<sup>2</sup>/l</p> <p>Fibreglass wallpaper, wallpapers for painting 5–7 m<sup>2</sup>/l</p>
<b>Dry time</b>	A painted surface is dry to the touch after 30 min and can be recoated after 1–2 h. Drying times are indicative and they depend on temperature, relative air humidity and ventilation.
<b>Tools</b>	Spray gun, roller or paintbrush
<b>Thinning</b>	Water
<b>Cleaning of tools</b>	Water
<b>Package sizes</b>	A bases 2.7 l, 9 l and 18 l, C bases 2.7 and 9 l tin can
<b>Transport</b>	No VAK classification
<b>EU VOC limit value</b>	Cat. A/d 30 g/l (2010), the ready-to use product's VOC max. 30 g/l