

FT-Card

5007 Fintex 7

Product	Matt, waterborne acrylate dispersion paint with good opacity.
Suitability	Can be used as primer or topcoat on walls and ceilings indoors. Suitable for concrete, plaster and filler surfaces along with various types of construction boards e.g. wood, chipboard, plywood, plasterboard, glass fibre wall coverings and paintable wallpapers. Usable for new and previously painted surfaces.
Properties	<p>excellent opacity</p> <p>solvent free</p> <p>A and C bases available, tintable with common tinting systems</p> <p>good rubbing resistance</p> <p>matt finish</p> <p>produced in Finland</p> <p>fulfills requirements for best indoor air classification M1</p>

Technical data

Dry contents	appr. 51 %	
Density	1,30 g/ml.	
Grade of gloss	RT5, (Finnish classification), matt.	
MT-group	MT314, (Finnish classification).	
Rubbing resistance	Good, stands more than 5000 brush strokes, SFS3455. SFS-EN 13300 class II, ISO11998.	
Tinting	Tintable according to common colour cards.	
Storage	36 months in original package, to be stored in dry, cool surroundings, temperature between +5...+25°C.	
Coverage	Previously painted surfaces	8-12 m ² /l
	Wood and construction boards	6-10 m ² /l
	Concrete, plaster and filler surfaces	5-7 m ² /l
	Fibre glass wall coverings and wallpapers	5-7 m ² /l
Drying time	Painted surface is dust dry in 30 minutes, repaintable after 2 hours. Drying times are estimated and dependable on temperature, relative humidity of air and ventilation.	
Tools	Spray gun, brush or roller.	
Thinning	Water.	
Cleaning of tools	Water.	
Package sizes	0,9, 2,7, 9 and 18 litres.	
Transportation	Non ADR-classified. Must be kept from freezing.	
EU VOC limit	cat.A/d 30g/l (2010), ready mixed product VOC max.30g/l.	

Instructions

Circumstances	Temperature must be over +5°C but under +25°C relative humidity of air below 80 %.
----------------------	--

FT-Card

Instructions

Remove dirt and dust from the surface to be painted. When required wash surfaces with 5059 Maalarin Tehopesu. Fill holes and cracks with Fintex-filler or with 1200 Tetramassa before painting. Apply 1-2 layers as required for lacquered inner ceilings 2-4 layers. Paint can be applied with a brush, roller or spray gun. It is recommended to use 5008 Fintex Stoppari as primer on old lacquered ceilings to block resins and branch marks. As topcoat it is recommended to use 5011 KattoPlus. Even after being most opaque there can still be some visual marks on painted surface within years. Always use proper protective clothing and protective device during paint work.

The information on this data sheet is based on laboratory tests and practical results. All test results are indicative. As we can not influence the working conditions and methods we are only responsible for the quality of the paint which is guaranteed in accordance with our high quality requirements. We are not liable for any damage caused by incorrect use of the product against instructions or if used for inappropriate purpose.

Environmental protection

Liquid paint is to be handled as hazardous waste. Empty, dry cans can be recycled or dealt as standard household waste.

Product safety

Contents of the product do not require any warning labels. A material safety data sheet is available.

Flammability

Non flammable.