

FT Card

5325 Fintex KSM25 TetraStop Antimicrobial Topcoat

Product Description	Semi-matte, low odor, water-based acrylic dispersion topcoat with high resistance to wear and moisture. A-paint base is white, and C-paint base appears milky in liquid form, drying to a colourless film.
Suitability	Suitable for use in areas requiring high hygiene, as a washable interior wall topcoat. Applicable on concrete, plaster, and filler surfaces. Also suitable for various wood, particle board, plywood, gypsum board, fiberglass, wallpaper, and previously painted ceilings and walls. Interior use only, including HVAC pipes and primed metal surfaces.
Features:	<p>Antimicrobial properties are based on silver, which prevents bacterial cell division and metabolism, inhibiting microbial growth.</p> <p>Antimicrobial effectiveness remains throughout the paint's lifespan.</p> <p>Excellent coverage.</p> <p>Highly durable, ideal for public spaces.</p> <p>Can be tinted with standard tinting systems.</p> <p>Non-yellowing white A-base.</p> <p>Part of the TetraStop system.</p> <p>Suitable for public facilities, laboratories, operating rooms, etc.</p> <p>Made in Finland.</p> <p>M1 certified.</p>

Technical Specifications

Solids content:	approx. 52%
Density:	1.30 g/ml
Gloss group:	RT4, semi-matte
Special feature:	Antimicrobial
Certifications:	ISO 22196:2011, M1
Wear resistance:	Excellent, SFS-EN 13300 Class I, ISO11998
Tinting:	Available for A- and C-bases
Storage:	36 months in original packaging, stored in a dry and cool place, between +5°C and +25°C.
Coverage:	<p>Previously painted surfaces: 8-12 m²/l</p> <p>Wood and panel surfaces: 6-10 m²/l</p> <p>Concrete, plaster, and filler surfaces: 5-7 m²/l</p> <p>Fiberglass and wallpaper: 5-7 m²/l</p>
Drying time:	Dust-free in 30 minutes, re-coatable in 2 hours. Times may vary depending on temperature, humidity, and ventilation.
Tools:	Spray, roller, or brush
Thinner:	Water
Tool cleaning:	Water
Available sizes:	0.9, 2.7, 9, and 18 litres
Transport:	Not classified as hazardous for transport
EU VOC limit:	cat. A/a 30 g/l (2010), max. 30 g/l for ready-to-use product

Application Instructions

Conditions:	Temperature should be over +5°C and under +25°C, with humidity below 80%.
Preparation:	Clean the surface from dirt and dust. If needed, wash surfaces with Maalarin Tehopesu. Fill cracks and holes with appropriate filler before painting. Apply 1-2 coats as needed, using a roller, brush, or spray. Use appropriate protective gear during the painting process.
Environmental Protection	Unused liquid paint should be taken to hazardous waste collection points. Empty, dry containers can be recycled or, if not possible, disposed of at a landfill.
Safety	A separate safety data sheet is available for the product. Not flammable.

+358 20 785 1210

FINTEX · TETRAKEM